



MODEL SERIES	COMPARTMENT CONFIGURATION	DEPTH	DOORS	INSTALLATION	CONTROLS
SWC-15	SINGLE	18" OR 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING OR COUNTER TOP	DIGITAL PROGRAMABLE WITH AVAILABLE KEYED LOCKOUT
SWC-28	SINGLE	18" OR 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING OR COUNTER TOP	DIGITAL PROGRAMABLE WITH AVAILABLE KEYED LOCKOUT
SWC-41	SINGLE	18" or 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING OR COUNTER TOP	DIGITAL PROGRAMABLE WITH AVAILABLE KEYED LOCKOUT
SWC-61	SINGLE	18" or 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING WITH OPTIONAL CASTERS	DIGITAL PROGRAMABLE WITH AVAILABLE KEYED LOCKOUT
SWC-1528	DOUBLE	18" or 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING WITH OPTIONAL CASTERS	DIGITAL PROGRAMABLE INDEPENDENT FOR EACH CABINET WITH AVAILABLE KEYED LOCKOUT
SWC-1541	DOUBLE	18" or 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING WITH OPTIONAL CASTERS	DIGITAL PROGRAMABLE INDEPENDENT FOR EACH CABINET WITH AVAILABLE KEYED LOCKOUT
SWC-2828	DOUBLE	18" or 24"	SOLID OR DUAL PANE LOW E GLASS	FREE STANDING WITH OPTIONAL CASTERS	DIGITAL PROGRAMABLE INDEPENDENT FOR EACH CABINET WITH AVAILABLE KEYED LOCKOUT

Standard Features

Temperature Range	Programable 90-160F
Data Recording	USB recorded, downloadable temperature and event memory
Door Locks	Standard keyed lock